

Interface module - FLK 26 - 2280051

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VARIOFACE module, with screw connection and flat-ribbon cable plug connector, for mounting on NS 32 or NS 35/7.5, with male connector and short and long locking latches for female connectors, 26-pos. (separate test socket for each channel)

The illustration shows a 20-position version



Key commercial data

Packing unit	1
Minimum order quantity	5
Catalog page	Page 242 (IF-2007)
GTIN	 4 017918 054311
Custom tariff number	85369010
Country of origin	GERMANY

Technical data

General data

Nominal voltage UN	< 50 V AC
Nominal voltage UN	60 V DC
Max. current carrying capacity per branch	1 A
Number of positions	26
Width	75.5 mm
Height	50 mm
Depth	58.5 mm
Status display	No
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage	800 V AC (50 Hz, 1 min.)
Mounting position	Any
Standards/regulations	IEC 60664
Standards/regulations	DIN EN 50178
Standards/regulations	IEC 62103
Pollution degree	2

Interface module - FLK 26 - 2280051

Technical data

General data

Surge voltage category	II
------------------------	----

Connection data for connection 1

Connection name	PCB connection
Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3

Classifications

eclass

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608

etim

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

unspsc

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

GOST

Interface module - FLK 26 - 2280051

Approvals

Ex Approvals

Approvals submitted

Approval details



Accessories

Accessories

Cable/conductor

Cable - FLK 26/EZ-DR/ 50/KONFEK - 2299385



Round cable set, with two 26-pos. socket strips, (1:1 connection), cable length: 0.5 m

Cable - FLK 26/EZ-DR/ 100/KONFEK - 2299398



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 1 m

Cable - FLK 26/EZ-DR/ 150/KONFEK - 2299408



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 1.5 m

Interface module - FLK 26 - 2280051

Accessories

Cable - FLK 26/EZ-DR/ 300/KONFEK - 2299424



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 3 m

Cable - FLK 26/EZ-DR/ 400/KONFEK - 2299437



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 4 m

Cable - FLK 26/EZ-DR/ 600/KONFEK - 2299440



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 6 m

Cable - FLK 26/EZ-DR/ 800/KONFEK - 2299453



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 8 m

Cable - FLK 26/EZ-DR/1000/KONFEK - 2299466



Round cable set, with two 26-pos. socket strips (1:1 connection), cable length: 10 m

Cable - FLK EZ-DR.../.../... - 2295059



Round cable, with preassembly, not shielded, variable cable length

Interface module - FLK 26 - 2280051

Accessories

Plug/Adapter

Reducing plug - RPS - 0201647



Reducing plug, Color: gray
