HellermannTyton



Article Number: 148-90004

Description: HelaCon Plus Push-In Style Wire Connector, Double Spring, 6-Port, Polycarbonate, Purple, 50/pkg

| Base Data | | |
|-----------------------------|-----------------------|---|
| | | |
| | Local Order Number | 148-90004 |
| | Туре | HECP-6 |
| | Color | Clear (CL) |
| | Features and benefits | Double Spring Technology for safe, secure and reliable connections Low Insertion Forces + High Retention Values Accommodates both solid and stranded wire cores Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards Low insertion forces reduces buckling of stranded wire Able to combine solid and stranded within same housing Separate test port for fast, easy confirmation of connection Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time. Max Current Rating to 24 A Max Voltage Rating to 600 V (c UL us) |
| | Product Description | Helacon Plus is a unique push-in wire connector with double spring technology. Double spring design requires less insertion force and delivers superior retention values. Helps alleviate repetitive motion injuries often associated with twist-on style connectors. |
| | Short Description | HelaCon Plus Push-In Style Wire Connector, Double Spring, 6-Port, Polycarbonate, Purple, 50/pkg |
| Product Dimensions | | |
| | Length L (Metric) | 19.0mm |
| | Max Current | 24A |
| | Max Voltage | 600V |
| | Number of Conductors | 6 |
| | Width W (Imperial) | 1.12" |
| | Width W (Metric) | 28.35mm |
| | Height H (Imperial) | 0.41" |
| | Height H (Metric) | 10.45mm |
| Material and Specifications | | |
| | Material | Polycarbonate (PC) |

148-90004

HellermannTyton

| Material and Specifications | Material Shortcut | PC |
|--------------------------------|------------------------------|----------------------------------|
| | Flammability | UL 94 V2 |
| | Halogenfree | Yes |
| | Operating Temperature | -22°F to +185°F (-30°C to +85°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| | Certification/Specification | FIMKO |
| | UL Listed (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 50 |
| | Package Quantity (Metric) | 50Pieces |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |
| | Weight (imperial) | 12.4oz |
| | Weight (Metric) | 0.68kg |