HellermannTyton

Specification Sheet

Part Number: 333-41506



Heat Shrink Tubing, Bulk Reel, 3:1 Shrink Ratio, 1.5", 39/13 Dia, PO, Black, 100 ft/reel

| Туре | |
|---------------------|---|
| | TFN31 39/13 |
| Color | Black (BK) |
| Features & Benefits | • Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters. • Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing). • Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels. • Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications. |
| Quantity Per | reel |

| Product Description | TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes. |
|------------------------------|--|
| Short Description | Heat Shrink Tubing, Bulk Reel, 3:1 Shrink Ratio, 1.5", 39/13 Dia, PO, Black, 100 ft/reel |
| Global Part Name | TFN31 39/13-PO-X-BK |
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.5 |
| Variant | Thin-Wall |
| Nominal Diameter (Imperial) | 1-1/2 |
| Nominal Diameter (Metric) | 39 |
| Wall Thickness WT (Imperial) | .049 |
| Wall Thickness WT (Metric) | 1.25 |
| | |

| Material | Polyolefin, cross-linked (PO-X) |
|-------------------|---------------------------------|
| Material Shortcut | PO-X |
| Flammability | UL 224 VW-1 |

| Halogen free | No |
|---------------------------------|---|
| Operating Temperature (Metric) | -67°F to +275°F (-55°C to +135°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | CSA C22.2 no. 198.1-06 UL ANSI/UL 224 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| | |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 30 |
| Customs Number | 3926909987 |

© 2018 HellermannTyton. All rights reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions