

C322C223F2G5TA Inventory

C322C223F2G5TA Order Online



Image may be representation. See specs for product details.

## C322C223F2G5TA

Manufacturer Part Number:	C322C223F2G5TA
Manufacturer/Brand:	KEMET
Part of Description:	CAP CER 0.022UF 200V COG RADIAL
Datasheets:	C322C223F2G5TA.pdf
RoHs Status:	Rohs Lead free / RoHS
Stock Condition:	Compliant New original, 2661 pcs Stock Available.
Ship From:	Hong Kong
Shipment Way:	DHL/Fedex/TNT/UPS/EMS

## Specifications

Manufacturer     KEMET       Description     CAP CER 0.022UF 200V COG RADIAL       Category     Capacitors > Ceramic Capacitors       Part Status     2661 pcs Stock       Voltage - Rated     200V       Tolerance     ±1%       Tindeness (Max)     -       Temperature Coefficient     COG, NPO       Size / Dimension     0.200° L x 0.125° W (5.08mm x 3.18mm)       Series     Goldmax, 300       Ratings     -       Package / Case     Radial       Operating Temperature     -55°C ~ 125°C       Mounting Type     Through Hole       Lead Style     Formed Leads - Kinked       Lead Style     Formed Leads - Kinked       Lead Style     Cole (6.60mm)       Height - Seated (Max)     0.220″ f C.80mm)       Height - Seated (Max)     0.220″ f C.80mm)       Height - Seated (Max)     0.220″ f C.80mm)	Part Number	C322C223F2G5TA
Category Capacitors > Ceramic Capacitors   Part Status 2661 pcs Stock   Voltage - Rated 200V   Tolerance ±1%   Thickness (Max) -   Temperature Coefficient COG, NPO   Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm)   Series Goldmax, 300   Ratings -   Package / Case Radial   Operating Temperature 55°C ~ 125°C   Mounting Type Through Hole   Lead Style Formed Leads - Kinked   Lead Style 0.200° (5.08mm)   Height - Seated (Max) 0.260° (6.60mm)   Features Low ESL   Faiture Rate -   Copacitance 0.022µF	Manufacturer	KEMET
Part Status 2661 pcs Stock   Voltage - Rated 200V   Tolerance ±1%   Thickness (Max) -   Temperature Coefficient C0G, NPO   Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)   Series Goldmax, 300   Ratings -   Package / Case Radial   Operating Temperature 55°C ~ 125°C   Mounting Type Through Hole   Lead Style Formed Leads - Kinked   Lead Style Solo" (5.08mm)   Height - Seated (Max) 0.260" (6.60mm)   Features Low FSL   Fallure Rate -   Capecitance 0.022µF	Description	CAP CER 0.022UF 200V COG RADIAL
Voltage - Rated200VTolerance±1%Thickness (Max)-Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 200Ratings-Package / CaseRadialOperature Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200° (5.08mm)Height - Seated (Max)0.260° (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.324jF	Category	Capacitors > Ceramic Capacitors
Tolerance±1%Thickness (Max)-Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Peckage / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Part Status	2661 pcs Stock
Thickness (Max)-Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (S.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-S5°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Style0.200" (S.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Voltage - Rated	200V
Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Style0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Tolerance	±1%
Size / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Style0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Thickness (Max)	_
SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200° (5.08mm)Height - Seated (Max)0.260° (6.60mm)FeaturesLow ESLFailure Rate-Capactance0.022µF	Temperature Coefficient	COG, NPO
Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.002µF	Series	Goldmax, 300
Operating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Ratings	-
Mounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Package / Case	Radial
Lead StyleFormed Leads - KinkedLead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Operating Temperature	-55°C ~ 125°C
Lead Spacing0.200" (5.08mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022µF	Mounting Type	Through Hole
Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance0.022μF	Lead Style	Formed Leads - Kinked
FeaturesLow ESLFailure Rate-Capacitance0.022µF	Lead Spacing	0.200" (5.08mm)
Failure Rate - Capacitance 0.022µF	Height - Seated (Max)	0.260" (6.60mm)
Capacitance 0.022µF	Features	Low ESL
	Failure Rate	-
Applications Bypass, Decoupling	Capacitance	0.022µF
	Applications	Bypass, Decoupling

## You May Be Also Be interested

C322C223F2G5TA Price

C322C223F2G5TA New

In:					
C322C223F3G5TA KEMET CAP CER 0.022UF 25V C0G RADIAL	<b>C322C223F2G5TA</b> KEMET CAP CER 0.022UF 200V COG RADIAL	<b>C322C222KCR5TA</b> KEMET CAP CER 2200PF 500V X7R RADIAL	<b>C322C223F1G5TA</b> KEMET CAP CER 0.022UF 100V COG RADIAL		
<b>C322C223F2G5TA7301</b> KEMET CAP CER 0.022UF 200V COG RADIAL	C322C222KAG5TA7301 KEMET CAP CER 2200PF 250V COG RADIAL	<b>C322C223F5G5TA</b> KEMET CAP CER 0.022UF 50V C0G RADIAL	<b>C322C222KAG5TA</b> KEMET CAP CER RAD 2.2NF 250V C0G 10%		
C322C223F2G5TA Related keyword					
C322C223F2G5TA KEMETC322C223F2G5TA Data SheetC322C223F2G5TA DatasheetsC322C223F2G5TA PDFKEMET C322C223F2G5TAC322C223F2G5TA ElectronicC322C223F2G5TA ComponentsC322C223F2G5TA DistributorC322C223F2G5TA ImageC322C223F2G5TA Part					

## Contact us: Info@YIC-Electronics.com

C322C223F2G5TA Picture

C322C223F2G5TA Warranted

C322C223F2G5TA Manufacturer

C322C223F2G5TA Original

ADD:Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.

C322C223F2G5TA Stock

C322C223F2G5TA RFQ

Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited