

## Panasonic

Image may be representation. See specs for product details. **Ship From:** 

**Shipment Way:** 

## 2SA10220BL Manufacturer Part Number: 2SA10220BL Manufacturer/Brand: Panasonic Part of Description: TRANS PNP 20V 0.03A MINI-3P Datasheets: 2SA10220BL.pdf RoHs Status: Contains lead / RoHS non-compliant Stock Condition: New original, 2501 pcs Stock Available.


Part Number         25A10220BL           Manufacturer         Panasonic           Description         TRANS PNP 20V 0.03A MINI-3P	Specifications	
Description TRANS PNP 20V 0.03A MINI-3P  Category.  Part Status 2501 pcs Stock  Voltage - Collector Emitter Breakdown (Max) 20V  Vce Saturation (Max) ⊕ Ib, Ic 100mV ⊕ 1mA, 10mA  Transistor Type PNP  Supplier Device Package Mini3-G1  Series -  Power - Max 200mW  Packaging Tape & Reel (TR)  Package / Case T0-236-3, SC-59, SOT-23-3  Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) ⊕ Ic, Vce 70 ⊕ 1mA, 10V	Part Number	2SA10220BL
Discrete Semiconductor Products > Transistors - Bipolar  2501 pcs Stock  Voltage - Collector Emitter Breakdown (Max)  20V  Vce Saturation (Max) @ Ib, Ic  100mV @ 1mA, 10mA  Transistor Type  PNP  Supplier Device Package  Mini3-G1  Series  -  Power - Max  200mW  Packaging  Tape & Reel (TR)  Package / Case  TO-236-3, SC-59, SOT-23-3  Operating Temperature  150°C (TI)  Mounting Type  Surface Mount  Frequency - Transition  300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce  70 @ 1mA, 10V	Manufacturer	Panasonic
Category Part Status 2501 pcs Stock  Voltage - Collector Emitter Breakdown (Max) 20V  Vce Saturation (Max) @ Ib, Ic 100mV @ 1mA, 10mA  Transistor Type PNP  Supplier Device Package Mini3-G1  Series - Power - Max 200mW  Packaging Tape & Reel (TR)  Package / Case TO-236-3, SC-59, SOT-23-3  Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Description	TRANS PNP 20V 0.03A MINI-3P
Part Status 2501 pcs Stock  Voltage - Collector Emitter Breakdown (Max) 20V  Vce Saturation (Max) @ Ib, Ic 100mV @ 1mA, 10mA  Transistor Type PNP  Supplier Device Package Min13-G1  Series - Power - Max 200mW  Packaging Tape & Reel (TR)  Package / Case TO-236-3, SC-59, SOT-23-3  Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Category	Discrete Semiconductor Products > Transistors - Bipolar
Vce Saturation (Max) @ Ib, Ic 100mV @ 1mA, 10mA   Transistor Type PNP   Supplier Device Package Mini3-G1   Series -   Power - Max 200mW   Packaging Tape & Reel (TR)   Package / Case TO-236-3, SC-59, SOT-23-3   Operating Temperature 150°C (TJ)   Mounting Type Surface Mount   Frequency - Transition 300MHz   DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V		2501 pcs Stock
Transistor Type PNP Supplier Device Package Mini3-G1 Series - Power - Max 200mW  Packaging Tape & Reel (TR)  Package / Case T0-236-3, SC-59, SOT-23-3 Operating Temperature 150°C (TJ)  Mounting Type Surface Mount Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Voltage - Collector Emitter Breakdown (Max)	20V
Supplier Device Package Mini3-G1  Series -  Power - Max 200mW  Packaging Tape & Reel (TR)  Package / Case TO-236-3, SC-59, SOT-23-3  Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Vce Saturation (Max) @ Ib, Ic	100mV @ 1mA, 10mA
Series         -           Power - Max         200mW           Packaging         Tape & Reel (TR)           Package / Case         TO-236-3, SC-59, SOT-23-3           Operating Temperature         150°C (TJ)           Mounting Type         Surface Mount           Frequency - Transition         300MHz           DC Current Gain (hFE) (Min) @ Ic, Vce         70 @ 1mA, 10V	Transistor Type	PNP
Power - Max  Packaging  Tape & Reel (TR)  Package / Case  TO-236-3, SC-59, SOT-23-3  Operating Temperature  150°C (TJ)  Mounting Type  Surface Mount  Frequency - Transition  300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce  70 @ 1mA, 10V	Supplier Device Package	Mini3-G1
Packaging Tape & Reel (TR)  Package / Case TO-236-3, SC-59, SOT-23-3  Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Series	-
Package / Case TO-236-3, SC-59, SOT-23-3  Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Power - Max	200mW
Operating Temperature 150°C (TJ)  Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Packaging	Tape & Reel (TR)
Mounting Type Surface Mount  Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Package / Case	TO-236-3, SC-59, SOT-23-3
Frequency - Transition 300MHz  DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Operating Temperature	150°C (TJ)
DC Current Gain (hFE) (Min) @ Ic, Vce 70 @ 1mA, 10V	Mounting Type	Surface Mount
	Frequency - Transition	300MHz
Current - Collector Cutoff (Max) 100uA	DC Current Gain (hFE) (Min) @ Ic, Vce	70 @ 1mA, 10V
Current - Collector Cutori (Max)	Current - Collector Cutoff (Max)	100μA

Hong Kong

DHL/Fedex/TNT/UPS/EMS

## You May Be Also Be interested

Current - Collector (Ic) (Max)






30mA














More

## 2SA10220BL Related keyword

2SA10220BL Panasonic 2SA10220BL Data Sheet 2SA10220BL Datasheets 2SA10220BL PDF Panasonic 2SA10220BL 2SA10220BL Components 2SA10220BL Image 2SA10220BL Electronic 2SA10220BL Distributor 2SA10220BL Part 2SA10220BL Price 2SA10220BL Manufacturer 2SA10220BL Picture 2SA10220BL Stock 2SA10220BL Inventory 2SA10220BL Order Online 2SA10220BL New 2SA10220BL Original 2SA10220BL Warranted 2SA10220BL RFQ