



Image may be representation. See specs for product details.

C321C119D3G5TA

Manufacturer Part Number:	C321C119D3G5TA		
Manufacturer/Brand:	KEMET		
Part of Description:	CAP CER 1.1PF 25V COG RADIAL		
Datasheets:	C321C119D3G5TA.pdf		
RoHs Status:	🦗 Lead free / RoHS		
Stock Condition:	Compliant New original, 2690 pcs Stock Available.		
Ship From:	Hong Kong		
Shipment Way:	DHL/Fedex/TNT/UPS/EMS		

Specifications

Manufacturer KEMET Description CAP CER 1.IPF 25V COG RADIAL Category Capacitors > Ceramic Capacitors Part Status 2690 pcs Stock Voltage - Rated 25V Tolerance 40.5pF Trickness (Max) - Temperature Coefficient COG, NPO Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm) Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm) Series Goldmax, 300 Ratings - Pockage / Casa Radial Operating Temperature 55°C ~ 125°C Mounting Type Through Hole Lad Style Formed Laads - Kinked Lead Stacing 0.250° (6.60mm) Height - Seated (Max) 0.260° (6.60mm) Fatures Low ESL Fatures Low ESL Fatures 1.19F Applicators Bypesx, Decoupling	Part Number	C321C119D3G5TA		
CategoryCapacitors > Ceramic CapacitorsPart Status2690 pcs StockVoltage - Rated25VTolerance±0.5pFThickness (Max)-Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SariesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Style0.260" (6.35mm)Height - Seated (Max)0.260" (6.60mn)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Manufacturer	KEMET		
Part Status 2690 pcs Stock Voltage - Rated 25V Tolerance ±0.5pF Thickness (Max) - Temperature Coefficient COG, NPO Size / Dimension D.200° L x 0.125° W (5.08mm x 3.18mm) Series Goldmax, 300 Ratings - Package / Case Radial Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Lead Style Formed Leads - Kinked Lead Style S25° (6.50mm) Height - Seated (Max) 0.260° (6.50mm) Features Low ESL Faiture Rate - Copacitance 1.1pF	Description	CAP CER 1.1PF 25V C0G RADIAL		
Voltage - Rated25VTolerance±0.5pFThickness (Max)-Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.250" (6.05mm)Height - Seated (Max)0.250" (6.60mm)FaituresLow ESLFaiture Rate-Capacitance1.1pF	Category	Capacitors > Ceramic Capacitors		
Tolerance±0.5pFThickness (Max)-Temperature CoefficientCOG, NPOStee / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)SeriessGoldmax, 300Ratings-Package / CaseRadialOperaturg Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.260° (6.60mm)Height - Seated (Max)0.260° (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Part Status	2690 pcs Stock		
Thickness (Max) - Temperature Coefficient COG, NPO Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Series Goldmax, 300 Ratings - Package / Case Radial Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Lead Style Formed Leads - Kinked Lead Spacing 0.250" (6.35mm) Height - Seated (Max) 0.260" (6.60mm) Features Low ESL Failure Rate - Capacitance 1.1pF	Voltage - Rated	25V		
Temperature CoefficientCOG, NPOSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Style0.250" (6.63mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Tolerance	±0.5pF		
Size / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead StyleColo" (6.60mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Thickness (Max)	-		
SeriesGoldmax, 300Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.250° (6.35mm)Height - Seated (Max)0.260° (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Temperature Coefficient	COG, NPO		
Ratings-Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.250° (6.35mm)Height - Seated (Max)0.260° (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)		
Package / CaseRadialOperating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.250" (6.35mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Series	Goldmax, 300		
Operating Temperature-55°C ~ 125°CMounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.250" (6.35mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Ratings	-		
Mounting TypeThrough HoleLead StyleFormed Leads - KinkedLead Spacing0.250" (6.35mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Package / Case	Radial		
Lead StyleFormed Leads - KinkedLead Spacing0.250" (6.35mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Operating Temperature	-55°C ~ 125°C		
Lead Spacing0.250" (6.35mm)Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Mounting Type	Through Hole		
Height - Seated (Max)0.260" (6.60mm)FeaturesLow ESLFailure Rate-Capacitance1.1pF	Lead Style	Formed Leads - Kinked		
FeaturesLow ESLFailure Rate-Capacitance1.1pF	Lead Spacing	0.250" (6.35mm)		
Failure Rate-Capacitance1.1pF	Height - Seated (Max)	0.260" (6.60mm)		
Capacitance 1.1pF	Features	Low ESL		
	Failure Rate	-		
Applications Bypass, Decoupling	Capacitance	1.1pF		
	Applications	Bypass, Decoupling		

You May Be Also Be interested

In:			
C321C119B3G5TA KEMET CAP CER 1.1PF 25V COG RADIAL	C321C120F3G5TA KEMET CAP CER 12PF 25V COG RADIAL	C321C119DAG5TA KEMET CAP CER 1.1PF 250V COG RADIAL	C321C120G3G5TA KEMET CAP CER 12PF 25V COG RADIAL
C321C119C3G5TA KEMET CAP CER 1.1PF 25V COG RADIAL	C321C112KAG5TA KEMET CAP CER RAD 1.1NF 250V COG 10%	C321C120GAG5TA KEMET CAP CER 12PF 250V COG RADIAL	C321C120FAG5TA KEMET CAP CER 12PF 250V COG RADIAL
C321C119D3G5TA Related k	9D3G5TA Data Sheet C321C119D3G5TA	Datasheets C321C119D3G5TA PDF	More KEMET C321C119D3G5TA

C321C119D3G5TA Electronic	C321C119D3G5TA Components	C321C119D3G5TA Distributor	C321C119D3G5TA Image	C321C119D3G5TA Part
C321C119D3G5TA Price	C321C119D3G5TA Manufacturer	C321C119D3G5TA Picture	C321C119D3G5TA Stock	C321C119D3G5TA Inventory
C321C119D3G5TA New	C321C119D3G5TA Original	C321C119D3G5TA Warranted	C321C119D3G5TA RFQ	C321C119D3G5TA Order Online

Contact us: Info@YIC-Electronics.com

ADD:Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.

Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited