

Image may be representation. See specs for product details.

C1210X112F4HACAUTO Manufacturer Part Number: C1210X112F4HACAUTO **Manufacturer/Brand: KEMET**

Part of Description: CAP CER 1210 1.1NF 16V ULTRA STA

C1210X112F4HACAUTO.pdf

RoHS Lead free / RoHS **RoHs Status:**

Datasheets:

Ship From:

Compliant **Stock Condition:** New original, 2506 pcs Stock Available.

Hong Kong

Shipment Way: DHL/Fedex/TNT/UPS/EMS

Specifications

Part Number C1210X112F9HACAUTO Manufacturer KEPHET Description CAP CER 1210 1.1NF 16V ULTRA STA Category Capacitors > Ceramic Capacitors Part Status 2506 pcs Stock Voltage - Rated 16V Tolerance ±1% Thickness (Max) 0.039* (0.98mm) Temperature Coefficient X8 Size / Dimension 0.130* L x 0.102* W (3.30mm x 2.60mm) Sames FF-CAP Batings AEC-Q200 Peckaging Tape & Real (TR) Peckaging Tape & Real (TR) Peckaging Tape & Real (TR) Peckaging Temperature -55°C ~ 150°C Mounting Type Surface Mount, PLCC Mounting Type Surface Mount, PLCC Mosture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Scated (Max) - Lead Free Status / RoHS Status Low Est., Soft Termination Failure Rate -	Specifications	
Description CAP CER 1210 1.1NF 16V ULTRA STA Catagory Capacitors > Ceramic Capacitors Part Status 2506 pcs Stock Voltage - Rated 16V Tolerance ±1½6 Thickmess (Max) 0.039° (10.98mm) Temperature Coefficient XSR Size / Dimension 0.130° L x 0.102° W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape 8.Real (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensibility Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seabed (Max) - Features Low ESL, Soft Termination Failure Rate - Description 1100pF ±1½ 16V Ceramic Capacitor XBR 1210 (3225	Part Number	C1210X112F4HACAUTO
Category Capacitors > Ceramic Capacitors Part Status 2506 pcs Stock Voltage - Fated 16V Tolerance ±156 Thickness (Max) 0.039" (0.98mm) Temperature Coefficient X8R Stee / Dimension 0.130" L x 0.102" W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape & Red (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESI, Soft Termination Falue Rate - Opperating Capacitor (Sepector)(Ion 1100pF ±1% 150 Ceramic Capacitor XSR 1210 (3225 Capacitance 1100pF	Manufacturer	KEMET
Part Status 2506 pcs Stock Voltage - Rated 16V Tolerance ±1% Thickness (Max) 0.039° (0.98mm) Temperature Coefficient X8R Size / Dimension 0.130° L x 0.102° W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Features 100pF ±1% 16V Ceramic Capacitor XSR 1210 (3225 Capacitance 1100pF ±1% 16V Ceramic Capacitor XSR 1210 (3225	Description	CAP CER 1210 1.1NF 16V ULTRA STA
Voltage - Rated 16V Tolerance ±1% Thickness (Max) 0.039" (0.98mm) Temperature Coefficient X8R Size / Dimension 0.130" k x 0.102" W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape & Reel (TR) Poerating Temperature 255°C x 150°C Operating Temperature 55°C x 150°C Mounting Type Surface Mount, MLCC Mounting Type 3 Weeks Lead Style 2 Lead Style 2 Lead Free Status / RoHS Status 1 Lead free / RoHS Compliant Height - Seated (Max) 2 Height - Seated (Max) 1 Low ESL, Soft Termination Fature Rate Low ESL, Soft Termination Fature Rate 1 Low ESL, Soft Termination Detailed Description 1 Loupf ± 1% 16V Ceramic Capacitor XBR 1210 (3225 Capacitance 1 Loupf	Category	Capacitors > Ceramic Capacitors
Tolerance ±1% Thickness (Max) 0.039" (0.98mm) Temperature Coefficient X8R Size / Dimension 0.130" L x 0.102" W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Free Status / RoHS Status Leaf free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Pallure Rate 1100pf ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pf	Part Status	2506 pcs Stock
Thickness (Max) 0.039" (0.98mm) Temperature Coefficient X8R Size / Dimension 0.130" L x 0.102" W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape 8. Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Mousture Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Peatures Low ESL, Soft Termination Failure Rate - Objet ±1% 16V Ceramic Capacitor XBR 1210 (3225 Capacitance 1100pF	Voltage - Rated	16V
Size / Dimension 0.130" L x 0.102" W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailled Description 1100pF ±1% 16V Ceramic Capacitor XSR 1210 (3225 Capacitance 1100pF	Tolerance	±1%
Size / Dimension 0.130" L x 0.102" W (3.30mm x 2.60mm) Series FT-CAP Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailled Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Thickness (Max)	0.039" (0.98mm)
Series FT-CAP Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Cepocitance 1100pF	Temperature Coefficient	X8R
Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature 55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description. 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Size / Dimension	0.130" L x 0.102" W (3.30mm x 2.60mm)
Packaging Tape & Reel (TR) Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor XSR 1210 (3225 Capacitance 1100pF	Series	FT-CAP
Package / Case 1210 (3225 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 1100pF	Ratings	AEC-Q200
Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Fallure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Packaging	Tape & Reel (TR)
Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description Capacitance 1100pF	Package / Case	1210 (3225 Metric)
Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Operating Temperature	-55°C ~ 150°C
Manufacturer Standard Lead Time 36 Weeks Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description Capacitance 1100pF 1100pF 1100pF	Mounting Type	Surface Mount, MLCC
Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Moisture Sensitivity Level (MSL)	1 (Unlimited)
Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Manufacturer Standard Lead Time	36 Weeks
Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Lead Style	-
Height - Seated (Max) - Features Low ESL, Soft Termination Failure Rate - Detailed Description 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 Capacitance 1100pF	Lead Spacing	-
Features Low ESL, Soft Termination Failure Rate - Detailed Description Capacitance 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225) 1100pF	Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Failure Rate - Detailed Description Capacitance 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 1100pF	Height - Seated (Max)	-
Detailed Description Capacitance 1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225 1100pF 1100pF	Features	Low ESL, Soft Termination
Detailed Description Capacitance 1100pF	Failure Rate	-
Capacitance 1100pF	Detailed Description	1100pF ±1% 16V Ceramic Capacitor X8R 1210 (3225
Applications Automotive, Boardflex Sensitive		1100pF
	Applications	Automotive, Boardflex Sensitive

You May Be Also Be interested


In:

STA


STA




C1210X112F8HAC7800 CAP CER 1210 1.1NF 10V ULTRA



C1210X112F3HAC7800 CAP CER 1210 1.1NF 25V ULTRA STA




C1210X112F4HAC7800 CAP CER 1210 1.1NF 16V ULTRA STA




C1210X112F5HAC7800 CAP CER 1210 1.1NF 50V ULTRA STA




C1210X112F8HACAUTO KEMET CAP CER 1210 1.1NF 10V ULTRA



C1210X112F3HACAUTO CAP CER 1210 1.1NF 25V ULTRA STA



C1210X112G1HAC7800 **KEMET** CAP CER 1210 1.1NF 100V **ULTRA ST**



C1210X112F5HACAUTO KEMET CAP CER 1210 1.1NF 50V ULTRA STA

C1210X112F4HACAUTO Related keyword

C1210X112F4HACAUTO KEMET C1210X112F4HACAUTO Electronic C1210X112F4HACAUTO Price

C1210X112F4HACAUTO New

C1210X112F4HACAUTO Components C1210X112F4HACAUTO Distributor C1210X112F4HACAUTO Manufacturer C1210X112F4HACAUTO Picture C1210X112F4HACAUTO Original

C1210X112F4HACAUTO Data Sheet C1210X112F4HACAUTO Datasheets C1210X112F4HACAUTO Warranted

C1210X112F4HACAUTO PDF C1210X112F4HACAUTO Image C1210X112F4HACAUTO Stock C1210X112F4HACAUTO RFQ

KEMET C1210X112F4HACAUTO C1210X112F4HACAUTO Part C1210X112F4HACAUTO Inventory C1210X112F4HACAUTO Order Online

More