



C1206C124K4JACAUTO Manufacturer Part Number: C1206C124K4JACAUTO Manufacturer/Brand: **KEMET Part of Description:** CAP CER 0.12UF 16V U2J 1206 **Datasheets:** C1206C124K4JACAUTO.pdf RoHS Lead free / RoHS **RoHs Status:** Compliant **Stock Condition:** New original, 2610 pcs Stock Available. **Ship From:** Hong Kong **Shipment Way:** DHL/Fedex/TNT/UPS/EMS

Part Number C1208C124KH3CAUTO Manufacturer KCMET Description CAP CER 0.12UF 18V U2J 1206 Category Capacitors > Ceremic Capacitors Part Status 25.10 pcs Stock Voltage - Rated 16V Tolerance ± 10% Titlichess (Placy) 0.53° (1.35mm) Perspectature Coefficient U2 Series C Ratings AEC (200 Packaging Tape & Red (TR) Packaging (See 1206 (2216 Mentric) Operating Temperature 55°C - 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Lulimited) Lead Spanding - Lead Free Status / ROHS Status Leaf free / ROHS Complaint Lead Free Status / ROHS Status Leaf free / ROHS Complaint Healther Rate Low Dissipation Factor, Low Esl. Failure Rate - Operations 0.12µF = 10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12µF Operations 0.12µF	Specifications	
Description CAP CER 0.12UF 16V UZI 1206 Categopy Capacitors > Ceramic Capacitors Part Status 2610 pcs Stock Voltage - Rated 16V Tolerance ±1096 Thickness (Max) 0.053° (1.35mm) Temperature Coefficient UZI Size / Dimension 0.126° L x 0.063° W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packaging Tape R Red (TR) Packaging Temperature 55° C ~ 125° C Mounting Type Surface Mount, MLCC Mounting Type Surface Mount, MLCC Mounting Type Surface Mount, MLCC Mounting Type L (Unlimited) Lead Spacing L (Unlimited) Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) Lead free / RoHS Compliant Height - Seated (Max) Lead free / RoHS Compliant Databled Description. O.12µF = 1096 16V Ceramic Capacitor UZI 1206 (3216 Copportance D.12µF = 1096 16V Ceramic Capacitor UZI 1206 (3216	Part Number	C1206C124K4JACAUTO
Category Capacitors > Ceramic Capacitors Part Status 2610 pcs Stock Voltage - Rated 16V Tolerance ±10% Thickness (Max) 0.053° (1.55mm) Temperature Coefficient U2J Size / Dimension 0.126° L x. 0.063° W (3.20mm x.1.60mm) Series C Ratings AEC-Q200 Packaging Tape 8. Recl (TR) Packaging 1206 (2216 Menc) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Spacing - Lead Free Status / Rolfs Status Lead free / Rolfs Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Falure Rate - Operating Dissiration 0.12µF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12µF	Manufacturer	KEMET
Part Status Z610 pcs Stock Voltage - Rated 16V Tolerance ±10% Thickness (Max) 0.053" (1.35mm) Temperature Coefficient U2J Stee / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Packaging Temperature 1206 (3216 Metric) Operating Temperature 552°C × 125°C Mounting Type 554°C × 125°C Mouting Type 1 (Unlimited) Lead Skyle - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Height - Seated (Max) Low Dissipation Factor, Low ESL Features Low Dissipation Factor, Low ESL Detailed Description 0.12µF ±10% 16V Ceramic Capactor U2J 1206 (3216 Capacitance 0.12µF	Description	CAP CER 0.12UF 16V U2J 1206
Voltage - Rated 16V Tolerance ±10% Thickness (Max) 0.653" (1.35mm) Temperature Coefficient U2J Size / Dimension 0.126" L x 0.663" W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Packaging Temperature -55°C ~ 125°C Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Spacing - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Fallure Rate 1.20% 15% 16% Ceramic Capacitor U2J 1206 (3216 Catalled Description 0.12µF ± 10% 16% Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12µF	Category	Capacitors > Ceramic Capacitors
Tolerance ±10% Trickness (Max) 0.053" (1.35mm) Temperature Coefficient U2 Stze / Dimension 0.126" k x 0.063" W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packagel (Tase) 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Free Status / RoHS Status Leaf free / RoHS Compilant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Faller Rate 0.12µF ± 10% 16V Ceramic Capacitor U2) 1206 (3216 Capacitance 0.12µF	Part Status	2610 pcs Stock
Thickness (Max) 0.053" (1.35mm) Temperature Coefficient U23 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packaging Tape 8 Reel (TR) Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed, Description 0.12µF ±10% 16V Ceramic Capacitor U2) 1206 (3216 Capacitance 0.12µF	Voltage - Rated	16V
Temperature Coefficient U21 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailled Description 0.12μF ±10% 16V Ceramic Capacitor U21 1206 (3216 Capacitance 0.12μF	Tolerance	±10%
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailled Description 0.12µF ±10% 16V Ceramic Capacitor U23 1206 (3216 Capacitance 0.12µF	Thickness (Max)	0.053" (1.35mm)
Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailled Description 0.12µF ±10% 16V Ceramic Capacitor U23 1206 (3216 Capacitance 0.12µF	Temperature Coefficient	U2J
Ratings AEC-Q200 Packaging Tape & Red (TR) Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Obtailed Description 0.12µF ±10% 16V Ceramic Capacitor U23 1206 (3216 Capacitance 0.12µF	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Packaging Tape & Reel (TR) Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description 0.12μF ±10% 16V Ceramic Capacitor U23 1206 (3216 Capacitance 0.12μF	Series	С
Package / Case 1206 (3216 Metric) Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style Lead Spacing Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) Features Low Dissipation Factor, Low ESL Fallure Rate Detailed Description O.12µF ±10% 16V Ceramic Capacitor U2) 1206 (3216 Capacitance	Ratings	AEC-Q200
Operating Temperature-55°C ~ 125°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Lead Style-Lead Spacing-Lead Free Status / RoHS StatusLead free / RoHS CompliantHeight - Seated (Max)-FeaturesLow Dissipation Factor, Low ESLFailure Rate-Detailed Description0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216Capacitance0.12μF	Packaging	Tape & Reel (TR)
Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Fallure Rate - 0.12µF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12µF	Package / Case	1206 (3216 Metric)
Moisture Sensitivity Level (MSL) 1 (Unlimited) Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description O.12µF ±10% 16V Ceramic Capacitor U2J 1206 (3216) Capacitance 0.12µF	Operating Temperature	-55°C ~ 125°C
Lead Style - Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description 0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12μF	Mounting Type	Surface Mount, MLCC
Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description 0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12μF	Moisture Sensitivity Level (MSL)	1 (Unlimited)
Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description 0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12μF	Lead Style	_
Height - Seated (Max) - Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description 0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12μF	Lead Spacing	_
Features Low Dissipation Factor, Low ESL Failure Rate - Detailed Description 0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Capacitance 0.12μF	Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Failure Rate - 0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Detailed Description Capacitance 0.12μF	Height - Seated (Max)	-
0.12μF ±10% 16V Ceramic Capacitor U2J 1206 (3216 Detailed Description Capacitance 0.12μF 0.12μF	Features	Low Dissipation Factor, Low ESL
Detailed Description Capacitance 0.12µF	Failure Rate	_
Capacitance 0.12µF	Detailed Description	0.12µF ±10% 16V Ceramic Capacitor U2J 1206 (3216
Applications Automotive		0.12µF
	Applications	Automotive

You May Be Also Be interested





C1206C124K4RACTU KEMET CAP CER 0.12UF 16V X7R 1206



C1206C124K3JACAUTO **KEMET** CAP CER 0.12UF 25V U2J 1206





C1206C124K4JAC7800 **KEMET** CAP CER 0.12UF 16V U2J 1206



C1206C124K5RAC7800 KEMET CAP CER 0.12UF 50V X7R 1206



C1206C124K5JAC7800 KEMET CAP CER 0.12UF 50V U2J 1206



C1206C124K3JAC7800 CAP CER 0.12UF 25V U2J 1206



C1206C124K2RACTU **KEMET** CAP CER 0.12UF 200V X7R 1206



C1206C124K5JACAUTO CAP CER 0.12UF 50V U2J 1206

C1206C124K4JACAUTO Related keyword

More

C1206C124K4JACAUTO KEMET C1206C124K4JACAUTO Electronic C1206C124K4JACAUTO Price C1206C124K4JACAUTO New

C1206C124K4JACAUTO Data Sheet C1206C124K4JACAUTO Datasheets C1206C124K4JACAUTO Components C1206C124K4JACAUTO Distributor C1206C124K4JACAUTO Manufacturer C1206C124K4JACAUTO Picture C1206C124K4JACAUTO Original C1206C124K4JACAUTO Warranted

C1206C124K4JACAUTO PDF C1206C124K4JACAUTO Image C1206C124K4JACAUTO Stock C1206C124K4JACAUTO RFO

KEMET C1206C124K4JACAUTO C1206C124K4JACAUTO Part C1206C124K4JACAUTO Inventory C1206C124K4JACAUTO Order Online